



Article No.	clevis pin	Ø Wire			DBS	Thread UNF	Ø Pin	W	X	Y	Z	SW	Lmin - Lmax	Weight [kg]	Break Load [kg]
		mm	Inch	Dye											
18200306*	S/G	3	1/8"	3	6.35	1/4"	6.3	15	8.0	-	14.0	9	140 - 213	0.12	1200
18200408	S/G	4	5/32"	-	7.50	5/16"	8.0	20	9.0	10.5	28.5	11	187 - 262	0.20	1550
18200508	S/G	5	3/16"	-	9.11	5/16"	8.0	20	9.0	10.5	28.5	11	189 - 264	0.21	2200
18200510	S/G	5	3/16"	-	9.11	3/8"	9.5	25	11.0	13	33.5	14	215 - 299	0.32	2440
182D0510	S/G	-	-	3/16"	10.85	3/8"	9.5	25	11.0	13	33.5	14	215 - 299	0.33	3365
18273210	S/G	5.6	7/32"	-	10.85	3/8"	9.5	25	11.0	13	33.5	14	227 - 311	0.37	3365
18200610	S/G	6	-	-	12.55	3/8"	9.5	25	11.0	13	33.5	14	209 - 292	0.39	3365
18200611	S/G	6	-	6	12.55	7/16"	11.0	25	13.0	13	34.0	15	247 - 342	0.50	4375
18200612	S/G	6	-	6	12.55	1/2"	12.7	30	14.0	15.5	39.0	17	268 - 374	0.70	5250
18201411	S/G	6.3	1/4"	-	12.55	7/16"	11.0	25	13.0	13	34.0	15	244 - 339	0.50	4375

18201412	S/G	6.3	1/4"	1/4"	12.55	1/2"	12.7	30	14.0	15.5	39.0	17	267 - 373	0.71	5370
18200711	S/G	7	9/32"	-	14.30	7/16"	11.0	25	13.0	13	34.0	15	243 - 338	0.53	4375
18200712	S/G	7	9/32"	7	14.30	1/2"	12.7	30	14.0	15.5	39.0	17	268 - 374	0.73	5900
18200812	S/G	8	5/16"	-	16.13	1/2"	12.7	30	14.0	15.5	39.0	17	268 - 374	0.76	5900
18230816	S/G	8	5/16"	8	16.13	5/8"	12.7	30	14.0	15.5	38.0	21	318 - 456	1.08	7300
18200816	S	8	5/16"	8	16.13	5/8"	15.9	40	17.5	20.5	39.0	21	323 - 461	1.31	8500
18200816L	S	8	5/16"	8	16.13	5/8"	15.9	40	17.5	20.5	47.0	21	331 - 469	1.34	8500
18203816	S	9.5	3/8"	-	17.85	5/8"	15.9	40	17.5	20.5	39.0	21	324 - 462	1.36	8550
18203816L	S	9.5	3/8"	-	17.85	5/8"	15.9	40	17.5	20.5	47.0	21	332 - 470	1.39	8550
18203820	S	9.5	3/8"	3/8"	17.85	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	1.85	10000
18201016	S	10	-	-	17.85	5/8"	15.9	40	17.5	20.5	39.0	21	324 - 462	1.36	8550
18201016L	S	10	-	-	17.85	5/8"	15.9	40	17.5	20.5	47.0	21	332 - 470	1.39	8550
18261020	S	10	-	-	17.85	3/4"	15.9	40	17.5	20.5	37.0	26	372 - 537	1.91	9500
18201020	S	10	-	-	17.85	3/4"	19.0	50	21.5	25.5	53.5	26	394 - 559	2.20	9500
18201020L	S	10	-	-	17.85	3/4"	19.0	50	21.5	25.5	53.5	26	394 - 559	2.20	9500
18271616L	S	11.1	7/16"	-	19.83	3/4"	15.9	40	17.5	20.6	45.0	26	375 - 541	1.98	11500
18271620	S	11.1	7/16"	-	19.83	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	2.26	11500
18271620L	S	11.1	7/16"	-	19.83	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	2.26	11500
18201220	S	12	-	-	20.00	3/4"	19.0	50	21.5	25.5	53.5	26	392 - 557	2.17	11000
18201220L	S	12	-	-	20.00	3/4"	19.0	50	21.5	25.5	53.5	26	392 - 557	2.17	11000
18201220HD	S	12	-	-	21.44	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	2.22	12500
18201320	S	12.7	1/2"	-	21.44	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	2.21	12035
18201320L	S	12.7	1/2"	-	21.44	3/4"	19.0	50	21.5	25.5	53.5	26	391 - 556	2.21	12035

18201322	S	12.7	1/2"	-	21.44	3/4"	22.2	60	24.0	30.5	67.0	26	410 - 575	2.80	12035
18201322L	S	12.7	1/2"	-	21.44	3/4"	22.2	60	24.0	30.5	67.0	26	410 - 575	2.80	12035
18212722	S	12.7	1/2"	-	21.44	7/8"	22.2	60	24.0	30.5	67.5	31	479 - 672	3.75	17075
18201422	S	14	9/16"	-	25.00	7/8"	22.2	60	24.0	30.5	67.5	31	478 - 671	3.83	16550
18201422L	S	14	9/16"	-	25.00	7/8"	22.2	60	24.0	30.5	67.5	31	478 - 671	3.83	16550
2017.02.03.JL															