



Article	Clevis Pin	Wire Ø			Ø Pin	Z	X	L0	Y	DBS	Weight	Break load
No.	Options	mm	inch	Dye	mm	mm	mm	mm	mm	mm	[kg]	[kg]
350003*	S/G	3	1/8"	3	6.3	17.6	7.0	43	8	6.35	0.04	1200
350004	S/G	4	5/32"	-	8.0	28.6	9.0	56	11	7.5	0.08	1550
WDDT410	S/G	4	-	4	9.5	34.8	11.0	71	13	9.11	-	2750
350005	S/G	5	3/16"	-	9.5	34.3	11.0	69	13	9.11	0.16	2350
WDDT510	S	5	-	5	9.5	33.8	11.0	70	13	10.85	0.19	3250
WDDT511	S	5	-	5	11.0	33.8	11.0	70	13	10.85	0.18	3250
350732	S/G	5.5	7/32"	-	11.0	34.8	13.0	74	13	10.85	0.17	3550
351106	S/G	6	-	6	11.0	34.8	13.0	74	13	10.85	0.27	5100
350006	S/G	6	-	6	12.7	39.2	14.0	78	16	12.55	0.33	5100
350014	S/G	6.3	1/4"	1/4"	12.7	39.2	14.0	82	16	12.55	0.28	4920
350007	S/G	7	9/32"	7	12.7	39.2	14.0	83	16	14.3	0.34	6500
351208	S/G	8	5/16"	8	12.7	37.2	14.0	84	16	16.13	0.68	7800
350008	S	8	5/16"	8	15.9	39.2	17.5	92	21	16.13	0.58	8550
350038	S	9.5	3/8"	3/8"	15.9	44.7	17.5	105	21	17.86	0.61	9900
355810	S/G	10	-	-	15.9	36.7	17.5	96	21	17.86	0.69	9400

350010	S	10	-	-	19.0	55.2	21.5	117	26	17.86	0.91	9400
WDDT1019	S	10	-	10	19.0	54.2	21.5	121	26	19.83	-	12850
350716	S	11.1	7/16"	-	19.0	53.2	21.5	121	26	19.83	0.93	11250
351912L	S	12	-	-	19.0	52.7	21.5	118	26	20.0	0.96	10600
350012	S/G	12	-	-	22.2	66.7	24.0	158	32	20.0	1.3	10600
350012HD	S	12	-	-	22.2	67.7	24.0	174	32	21.42	1.65	12550
WDDT12222	S	12	-	12	22.2	68.2	24.0	154	32	25.0	1.77	17500
353412	S	12.7	1/2"	-	19.0	53.7	21.5	128	26	21.44	1.2	13100
357812	S	12.7	1/2"	-	22.2	67.7	24.0	158	32	21.42	1.4	13100
351914	S	14	9/16"	-	19.0	51.7	21.5	131	26	25.0	1.4	16550
357814	S	14	9/16"	-	22.2	66.7	24.0	144	32	25.0	1.4	16550
352514L	S	14	9/16"	-	25.4	66.5	28.0	155	32	25.0	2.2	26006
350016	S	16	5/8"	-	25.4	63.5	28.0	160	32	28.17	2.8	21350
352816L	S	16	5/8"	-	28.5	84.3	31.5	180	37	28.17	2.9	21350
350019	S	19	3/4"	-	28.5	70.7	31.5	170	37	34.5	3.1	30150
350019L	S	19	3/4"	-	28.5	77.7	31.5	177	37	34.5	3.4	30150
353219	S	19	3/4"	-	31.8	82.9	36.5	177	42	34.52	4.4	32400
350022	S	22	7/8"	-	31.8	84.9	36.5	187	42	40.46	5.0	35250
350026	S	25 - 26	1"	-	34.9	97.5	42.0	228	47	46.02	7.2	52200
350026L	S	25 - 26	1"	-	34.9	97.5	42.0	228	47	46.02	7.2	52200

S=Clevis Pin w/Split, G=Clevis Pin w/G-ring