



Article	Wire Ø			Thread	Ø Pin	Z	X	Y	T	DBS	D0	Lmin.- Lmax.	Weight	Break load
	No.	mm	inch											
14200306*	3	3	1/8"	3	M6	6.3	14.0	8.0				175 - 247	0.090	1200
14200408	4	4	5/32"	-	M8	8.0	26.0	10.5				223 - 299	0.169	1550
14200508	5	5	3/16"	-	M8	8.0	26.0	10.5				231 - 307	0.178	2350
14200510	5	5	3/16"	-	M10	9.5	29.0	12.0				258 - 343	0.327	2350
14200612	6	6	-	6	M12	12.7	35.5	15.5				320 - 429	0.609	5100
14200714	7	7	9/32"	7	M14	12.7	34.0	15.5				352 - 470	0.728	6000
14230816	8	8	5/16"	8	M16	12.7	33.0	15.5				381 - 520	1029	7500
14200816	8	8	5/16"	8	M16	16.0	34.5	18.0				388 - 520	1192	8300
14261020	10	10	-	-	M20	16.0	32.0	18.0				449 - 604	1784	9430
14201020	10	10	-	-	M20	19.0	36.5	22.0				458 - 613	1971	9430
14201220	12	12	-	-	M20	19.0	36.5	22.0				498 - 653	2057	10600
14201220HD	12	12	-	-	M20	19.0	36.5	22.0				483 - 638	2038	12550

* marked toggle