



Article	Ø Wire			Thread	Ø Pin	W	X	Y	Z	SW	DBS	Lmin - Lmax	DBS before swaging	Weight	Break Load
No.	mm	Inch	Dye	UNF	mm	mm	mm	mm	mm	mm	mm	mm	mm	[Kg]	[Kg]
17200306	3	1/8"	3	1/4"	6.3	13.0	7.0	7.5	13.5			134.5 - 208.5	6.22 - 6.35	0.106	1200
17200408	4	5/32"	-	5/16"	8.0	17.0	8.0	9.5	17.0			157.0 - 241.0	7.42 - 7.50	0.174	1550
17200510	5	3/16"	-	3/8"	9.5	19.0	10.0	11.0	20.0			176.5 - 272.5	9.00 - 9.11	0.329	2350
17200610	6	-	-	3/8"	9.5	19.0	10.0	11.0	20.0			179.0 - 275.0	12.42 - 12.55	0.365	3650
17200611	6	-	6	7/16"	11.0	24.0	12.0	12.5	23.5			207.0 - 315.0	12.42 - 12.55	0.396	4750
17200712	7	9/32"	7	1/2"	12.7	25.0	14.5	14.0	26.0			230.5 - 349.5	14.18 - 14.30	0.592	6400
17230816	8	5/16"	8	5/8"	12.7	29.0	17.0	15.0	32.0			284.0 - 435.0	16.01 - 16.13	1002	8580
17200816	8	5/16"	8	5/8"	16.0	33.0	17.0	17.5	35.0			286.0 - 437.0	16.01 - 16.13	1116	8580

17261020	10	-	-	3/4"	16.0	36.0	20.0	19.0	40.0			330.0 - 511.0	17.73 - 17.86	1686	9430
17201020	10	-	-	3/4"	19.0	40.0	20.0	21.5	49.0			335.0 - 516.0	17.73 - 17.86	1689	9430
17201220	12	-	-	3/4"	19.0	40.0	20.0	21.5	49.0			351.0 - 515.0	19.95 - 20.00	1925	11000
17201220HD	12	-	-	3/4"	19.0	45.0	20.0	21.5	49.0			328.0 - 509.0	21.31 - 21.44	2026	13250
17201422	14	9/16"	-	7/8"	22.0	45.0	24.0	26.0	54.0			401.0 - 613.0	24.88 - 25.00	3266	16550