



| Article | Wire Ø | Ø Pin | Ø Hole | X2 | Z2 | X1 | Z0 | Y1 | Z1 | Weight | Break Load |
|---------|--------|-------|--------|------|------|------|-------|------|------|--------|------------|
| No. | mm | mm | mm | mm | mm | mm | mm | mm | mm | [kg] | [kg] |
| 810005 | 2.5 | 5.0 | 5.1 | 7.0 | 11.5 | 5.0 | 23.0 | 7.0 | 7.5 | 0.019 | 1500 |
| 810006 | 3.0 | 6.3 | 6.45 | 7.0 | 13.5 | 6.0 | 30.0 | 10.0 | 12.0 | 0.031 | 1950 |
| 810008 | 4.0 | 8.0 | 8.1 | 8.2 | 17.0 | 7.5 | 36.3 | 11.5 | 12.5 | 0.061 | 3550 |
| 810010 | 5.0 | 9.5 | 9.6 | 10.0 | 20.0 | 8.5 | 43.0 | 13.0 | 13.0 | 0.092 | 4100 |
| 810011 | 6.0 | 11.0 | 11.1 | 12.0 | 23.5 | 10.0 | 47.5 | 14.5 | 14.5 | 0.137 | 5950 |
| 810012 | 7.0 | 12.7 | 12.8 | 14.4 | 26.0 | 11.0 | 50.0 | 16.0 | 16.0 | 0.180 | 6550 |
| 810016 | 8.0 | 16.0 | 16.2 | 17.0 | 35.0 | 12.0 | 72.0 | 17.0 | 23.0 | 0.317 | 7600 |
| 815820 | 8.0 | 16.0 | 16.2 | 20.0 | 40.0 | 15.0 | 80.0 | 20.5 | 31.5 | 0.514 | 12700 |
| 810020 | 12.0 | 19.0 | 19.2 | 20.0 | 49.0 | 18.0 | 94.0 | 20.5 | 25.5 | 0.653 | 13150 |
| 810022 | 12.0 | 22.2 | 22.2 | 24.0 | 54.0 | 20.0 | 120.0 | 25.0 | 48.0 | 1.040 | 21850 |