



Article	Wire Ø			Thread	Ø Pin	Z	Y	X	D0	W	Lmin.-Lmax.	Weight	Break load
No.	mm	inch	Dye	metric	mm	mm	mm	mm	mm	mm	mm	[kg]	[kg]
11200255	2.5	3/32"	-	M5	5.0	11.5		7.0			152 - 216	0.048	825
11250306	3	1/8"	3	M6	5.0	11.5		7.0			169 - 241	0.074	1200
11200306	3	1/8"	3	M6	6.3	13.0		7.0			171 - 243	0.079	1200
11250406	4	5/32"	-	M6	5.0	11.5		7.5			180 - 252	0.076	1300
11200406	4	5/32"	-	M6	6.3	13.0		7.0			178 - 250	0.083	1300
11200408	4	5/32"	-	M8	8.0	17.0		8.0			199 - 275	0.145	1550
11200508	5	3/16"	-	M8	8.0	17.0		8.0			207 - 283	0.154	2350
11280510	5	3/16"	-	M10	8.0	17.0		8.0			223 - 308	0.245	2350
11200510	5	3/16"	-	M10	9.5	19.0		10.5			225 - 310	0.250	2350
11200610	6	-	-	M10	9.5	19.0		10.5			243 - 328	0.291	3750
11200612	6	-	6	M12	12.7	25.0		14.5			288 - 397	0.505	5100
11200714	7	9/32"	7	M14	12.7	25.0		14.5			317 - 435	0.586	6000
11200814	8	5/16"	-	M14	12.7	25.0		14.5			337 - 455	0.634	6000
11230816	8	5/16"	8	M16	12.7	32.5		17.0			368 - 500	0.868	8300
11200816	8	5/16"	8	M16	16.0	35.0		17.0			370 - 502	0.944	7575

11261016	10	-	-	M16	16.0	35.0		17.0			391 - 523	1105	8300
11261020	10	-	-	M20	16.0	39.5		20.0			434 - 589	1545	9430
11201020	10	-	-	M20	19.0	45.0		20.0			439 - 594	1688	9430
11201220	12	-	-	M20	19.0	45.0		20.0			464 - 619	1774	11000
11201220HD	12	-	-	M20	19.0	45.0		20.0			449 - 604	1755	12800
11201424	14	9/16"	-	M24	25.0	66.0		26.0			600 - 800	3950	16550