



Article	Wire Ø			Thread	D	A	B	C	E	Lmin.-Lmax.	Weight	Break load
No.	mm	inch	Dye	metric	mm	mm	mm	mm	mm	mm	[kg]	[kg]
14100306*	3	1/8"	3	M6	6.3	13.0	7.0	14.0	8.0	150 - 222	0.099	1200
14100408	4	5/32"	-	M8	8.0	17.0	8.0	26.0	10.5	197 - 273	0.193	2200
14100510	5	3/16"	-	M10	9.5	19.0	10.0	29.0	12.0	226 - 311	0.362	3550
14100612	6	-	6	M12	12.7	25.0	14.5	35.5	15.5	285 - 394	0.671	5250
14100714	7	9/32"	7	M14	12.7	25.0	14.5	34.0	15.5	306 - 424	0.775	6000
14130816	8	5/16"	8	M16	12.7	32.5	17.0	33.0	15.5	337 - 469	1009	7500
14100816	8	5/16"	8	M16	16.0	35.0	17.0	35.0	18.0	346 - 478	1312	8300
14161020	10	-	-	M20	16.0	39.5	20.0	32.0	18.0	394 - 549	2003	12800
14101020	12	-	-	M20	19.0	45.0	20.0	36.5	22.0	408 - 563	2146	12800

* marked toggle